



*Synthetic absorbable PGLA suture.
Braided and coated*

CHARACTERISTICS

Predictable and constant absorption profile
Excellent knot tying
Minimum tissue reaction
Perfect caliber uniformity
Excellent handling
Minimum memory

INDICATIONS

Gey910 is indicated for use in superficial soft tissues. Approximation and ligation of skin and mucosa. For ophthalmic surgery, peripheral nerves anastomosis and vessels micro surgery. Cardiovascular tissues applications are not define

IN VIVO TENSILE STRENGTH

14 days **75%**
21 days **45%**

COMPLETE ABSORPTION

56/70 days

STERILIZATION

ETO (Ethilene Oxide)

COLORING

Violet or un dyed



Sutura sintetica absorbabila din acid glicolic si lactic. Sutura impletita si acoperita.

CARACTERISTICI

Profil de absorbtie predictibil si constant
Rezistenta excelenta a nodului
Reactie minima a tesutului
Uniformitatea diametrului
Manevrabilitate excelenta
Memorie minima

INDICATII

Suturile chirurgicale Gey910 sunt indicate pentru tesuturi moi, pentru apropierea si ligaturarea pielii si mucoasei, in chirurgia oftalmologica. Pentru anastomoza nervilor periferici si microchirurgia vasculara. Aplicarea pentru tesuturile cardio vasculare nu a fost inca definita.

REZISTENTA LA TRACTIUNE (RUPERE)

14 zile **75%**
21 zile **45%**

ABSORBTIE COMPLETA

56/70 zile

STERILIZARE

ETO oxid de etilena

CULOARE

Violet sau nevopsita

100%

**TENSILE STRENGTH GRAPHIC (%)****GRAFICUL MENTINERII REZISTENTEI LA INTINDERE**

COMPLETE ABSORPTION
ABSORBTIE COMPLETA

0%

56-70 DAYS/ZILE



Gey910

Genko
ITALIA

SPOOL (FREE SUTURE) FIR LIBER





DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	4-0	3-0	2-0	0	1	2
		(1.5)	(2)	(3)	(3.5)	(4)	(5)
150 V	P4-0V150L	P3-0V150L	P2-0V150L	POV150L	P1V150L	P2V150L	
250 V	P4-0V250L	P3-0V250L	P2-0V250L	POV250L	P1V250L	P2V250L	

PRE-CUT SUTURES FIR PRETAIAT

6X45	45 V	P4-0V6X45P	P3-0V6X45P	P2-0V6X45P	POV6X45P	P1V6X45P	P2V6X45P
12X45	45 V	P4-0V12X45P	P3-0V12X45P	P2-0V12X45P	POV12X45P	P1V12X45P	P2V12X45P



REVERSE CUTTING CU TAIETURA IN EXTERIOR






DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	6-0	5-0	4-0	3-0	2-0	0
		(0.7)	(1)	(1.5)	(2)	(3)	(3.5)
3/8 BENDING - CURBURA							
▼  DS 13 D	45 V		P5-0V45DS13D	P4-0V45DS13D			
▼  DS 16	75 I		P5-0I75DS16	P4-0I75DS16	P3-0I75DS16		
▼  DS 19	45 I		P5-0I45DS19	P4-0I45DS19	P3-0I45DS19		
	75 I		P5-0I75DS19	P4-0I75DS19	P3-0I75DS19		
▼  DS 24	75 I			P4-0I75DS24	P3-0I75DS24	P2-0I75DS24	






Gey910

Genko
ITALIA

REVERSE CUTTING CU TAIETURA IN EXTERIOR

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP							
	cm COLOR CULOARE	4-0 (1.5)	3-0 (2)	2-0 (3)	0 (3.5)	1 (4)	2 (5)	3 (6)
	3/8 BENDING - CURBURA							
 DS 26	75 I		P3-0I75DS26	P2-0I75DS26				
	45 V		P3-0V45DS26	P2-0V45DS26				
 DS 30	75 I			P2-0I75DS30	P0I75DS30	P1I75DS30		
 DS 36	75 I			P2-0I75DS36	P0I75DS36	P1I75DS36		
 DS 39	75 I			P2-0I75DS39	P0I75DS39	P1I75DS39		
 DS 45	75 I			P2-0I75DS45	P0I75DS45	P1I75DS45	P2I75DS45	



	cm COLOR CULOARE	3-0 (2)	2-0 (3)	0 (3.5)	1 (4)	2 (5)
	1/2 BENDING - CURBURA					
 HS 22	75 I			P0I75HS22	P1I75HS22	P2I75HS22
 HS 26 H HEAVY - RAMFORSAT	75 I		P2-0I75HS26H	P0I75HS26H	P1I75HS26H	
 HS 37 H HEAVY - RAMFORSAT	75 V		P2-0V75HS37H	P0V75HS37H	P1V75HS37H	
	90 V		P2-0V90HS37H	P0V90HS37H	P1V90HS37H	



Gey910



Genko
ITALIA

REVERSE CUTTING CU TAIETURA IN EXTERIOR

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP					
	cm COLOR CULOARE	3-0	2-0	0	1	2
		(2)	(3)	(3.5)	(4)	(5)
1/2 BENDING - CURBURA						
 HS 40	75 V			POV75HS40	P1V75HS40	P2V75HS40
	90 V			POV90HS40	P1V90HS40	P2V90HS40
 HS 48	75 V			POV75HS48	P1V75HS48	P2V75HS48
	90 V			POV90HS48	P1V90HS48	P2V90HS48

cm COLOR CULOARE	5-0	4-0	3-0	2-0	0	1
	(1)	(1.5)	(2)	(3)	(3.5)	(4)

STRAIGHT - DREPT

 GS 13	45 V		P4-0V45GS13			
 GS 45	45 I		P4-0I45GS45	P3-0I45GS45		
 GS 55	75 I			P3-0I75GS55	P2-0I75GS55	
 GS 60	75 V			P3-0V75GS60	P2-0V75GS60	
	75 I			P3-0I75GS60	P2-0I75GS60	









Gey910

Genko
ITALIA

REVERSE CUTTING
PRECISION POINT/MICRO POINT

CU TAIETURA IN EXTERIOR
TRIUNGHI INVERS (VARF IN JOS) PRECIZIE

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	6-0 (0.7)	5-0 (1)	4-0 (1.5)	3-0 (2)	2-0 (3)	0 (3.5)
	3/8 BENDING - CURBURA						
▼  DSM 11	45 I	P6-0I45DSM11	P5-0I45DSM11	P4-0I45DSM11			
▼  DSM 11 D	45 I			P4-0I45DSM11D			
▼  DSM 16	45 I		P5-0I45DSM16	P4-0I45DSM16			
▼  DSM 19	45 I		P5-0I45DSM19	P4-0I45DSM19	P3-0I45DSM19		
▼  DSM 24	45 I			P4-0I45DSM24	P3-0I45DSM24	P2-0I45DSM24	
▼  DSM 26	45 I				P3-0I45DSM26	P2-0I45DSM26	
	75 I				P3-0I75DSM26	P2-0I75DSM26	


cm COLOR CULOARE	10-0 (0.2)	9-0 (0.3)	8-0 (0.4)	7-0 (0.5)	6-0 (0.7)
------------------------	---------------	--------------	--------------	--------------	--------------

1/2 BENDING - CURBURA

▼  HSM 8 D	30 V			P8-0V30HSM8D		
---	------	--	--	--------------	--	--



CONVENTIONAL CUTTING
CU TAIETURA CONVENTIONALA

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP					
	cm COLOR CULOARE	6-0 (0.7)	5-0 (1)	4-0 (1.5)	3-0 (2)	2-0 (3)
	3/8 BENDING - CURBURA					
▲  DC 13	45 I	P6-0I45DC13	P5-0I45DC13			



Gey910



CONVENTIONAL CUTTING CU TAIETURA CONVENTIONALA

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	5-0	4-0	3-0	2-0	0	1
		(1)	(1.5)	(2)	(3)	(3.5)	(4)
3/8 BENDING - CURBURA							
	45 I	P5-0I45DC16	P4-0I45DC16	P3-0I45DC16			
	75 V	P5-0V75DC16	P4-0V75DC16	P3-0V75DC16			
	45 I		P4-0I45DC19	P3-0I45DC19			

1/2 BENDING - CURBURA							
	45 I			P3-0I45HC22			
	45 V		P4-0V45HC22	P3-0V45HC22			

5/8 BENDING - CURBURA							
	75 I			P3-0I75FC26			

CONVENTIONAL CUTTING PRECISION POINT/MICRO POINT

CU TAIETURA CONVENTIONALA TRIUNGHI CONVENTIONAL (VARF IN SUS) PRECIZIE

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	5-0	4-0	3-0	2-0	0	1
		(1)	(1.5)	(2)	(3)	(3.5)	(4)
3/8 BENDING - CURBURA							
	45 I	P5-0I45DCM16	P4-0I45DCM16	P3-0I45DCM16			
	45 I		P4-0I45DCM19	P3-0I45DCM19			
	75 I		P4-0I75DCM19	P3-0I75DCM19			
	45 I		P4-0I45DCM26	P3-0I45DCM26	P2-0I45DCM26		
	75 I		P4-0I75DCM26	P3-0I75DCM26	P2-0I75DCM26		
	75 I			P3-0I75DCM36	P2-0I75DCM36		






Gey910







Genko

ITALIA

TAPER POINT CU VARF ASCUTIT

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP							
	cm COLOR CULOARE	10-0 (0.2)	9-0 (0.3)	8-0 (0.4)	7-0 (0.5)	6-0 (0.7)	5-0 (1)	4-0 (1.5)
3/8 BENDING - CURBURA								
 DR 9	30 V			P8-0V30DR9		P6-0V30DR9		
	15 V	P10-0V15DR9						
 DR 13	60 V							P4-0V60DR13
	cm COLOR	7-0 (0.5)	6-0 (0.7)	5-0 (1)	4-0 (1.5)	3-0 (2)	2-0 (3)	0 (3.5)
 DR 17	45 V				P4-0V45DR17			

cm COLOR CULOARE	6-0 (0.7)	5-0 (1)	4-0 (1.5)	3-0 (2)	2-0 (3)	0 (3.5)	1 (4)











1/2 BENDING - CURBURA								
 HR 13	45 I	P6-0I45HR13	P5-0I45HR13					
	75 V	P6-0V75HR13	P5-0V75HR13					
 HR 13 HEAVY - RAMFORSAT	75 V					P2-0V75HR13H		
 HR 17	75 V		P5-0V75HR17	P4-0V75HR17	P3-0V75HR17			
 HR 20	75 V			P4-0V75HR20	P3-0V75HR20	P2-0V75HR20		
 HR 22	75 V			P4-0V75HR22	P3-0V75HR22	P2-0V75HR22		
	45 V			P4-0V45HR22	P3-0V45HR22	P2-0V45HR22		
 HR 26	75 V			P4-0V75HR26	P3-0V75HR26	P2-0V75HR26	POV75HR26	
	45 V			P4-0V45HR26	P3-0V45HR26	P2-0V45HR26	POV45HR26	P1V45HR26



Gey910

Genko
ITALIA

TAPER POINT CU VARF ASCUTIT

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	4-0	3-0	2-0	0	1	2
		(1.5)	(2)	(3)	(3.5)	(4)	(5)
1/2 BENDING - CURBURA							
 HR 27 H HEAVY - RAMFORSAT	75 V			P2-0V75HR27H	POV75HR27H	P1V75HR27H	P2V75HR27H
	90 V				POV90HR27H	P1V90HR27H	P2V90HR27H
 HR 30	75 V		P3-0V75HR30	P2-0V75HR30	POV75HR30	P1V75HR30	
 HR 30 H HEAVY - RAMFORSAT	75 V				POV75HR30H	P1V75HR30H	
 HR 30 D	75 V		P3-0V75HR30D	P2-0V75HR30D			
	100 V			P2-0V100HR30D			
 HR 37	75 V			P2-0V75HR37	POV75HR37	P1V75HR37	
	90 V			P2-0V90HR37	POV90HR37	P1V90HR37	
 HR 37 H HEAVY - RAMFORSAT	75 V			P2-0V75HR37H	POV75HR37H	P1V75HR37H	P2V75HR37H
	90 V			P2-0V90HR37H	POV90HR37H	P1V90HR37H	P2V90HR37H
 HR 40	75 V			P2-0V75HR40	POV75HR40		
 HR 40 H HEAVY - RAMFORSAT	75 V				POV75HR40H	P1V75HR40H	P2V75HR40H
	90 V				POV90HR40H	P1V90HR40H	P2V90HR40H
 HR 45 H HEAVY - RAMFORSAT	75 V				POV75HR45H	P1V75HR45H	P2V75HR45H
 HR 48 H HEAVY - RAMFORSAT	75 V				POV75HR48H	P1V75HR48H	P2V75HR48H
	90 V				POV90HR48H	P1V90HR48H	P2V90HR48H




Gey910

Genko
ITALIA


TAPER POINT CU VARF ASCUTIT

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm	4-0	3-0	2-0	0	1	2
	CULOARE	(1.5)	(2)	(3)	(3.5)	(4)	(5)

1/2 BENDING - CURBURA

 HR 65 H HEAVY - RAMFORSAT	75 V			P2-0V75HR65H	POV75HR65H	P1V75HR65H	P2V75HR65H
	90 V				POV90HR65H	P1V90HR65H	P2V90HR65H




 HR 80 H	100 V			P2-0V100HR80H	POV100HR80H	P1V100HR80H	
--	--------------	--	--	---------------	-------------	-------------	--



cm	3-0	2-0	0	1	2
CULOARE	(2)	(3)	(3.5)	(4)	(5)


5/8 BENDING - CURBURA

 FR 27 H HEAVY - RAMFORSAT	75 V	P3-0V75FR27H	P2-0V75FR27H	POV75FR27H	P1V75FR27H	
---	-------------	--------------	--------------	------------	------------	--

HEAVY - RAMFORSAT

 FR 27 HD HEAVY - RAMFORSAT	90 V			POV90FR27HD	P1V90FR27HD	
--	-------------	--	--	-------------	-------------	--

HEAVY - RAMFORSAT

 FR 37	75 V		P2-0V75FR37	POV75FR37	P1V75FR37	
--	-------------	--	-------------	-----------	-----------	--

 FR 40	75 V			POV75FR40	P1V75FR40	
--	-------------	--	--	-----------	-----------	--



Gey910

TAPER POINT CU VARF ASCUTIT

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP					
	cm COLOR CULOARE	5-0 (1)	4-0 (1.5)	3-0 (2)	2-0 (3)	0 (3.5)

5/8 BENDING - CURBURA

<p>FR 110 H</p> <p>HEAVY - RAMFORSAT</p>	75 V						P1V75FR110H
--	-------------	--	--	--	--	--	-------------

J NEEDLE – AIGUILLE A J

<p>JR 22</p>	75 V		P4-0V75JR22	P3-0V75JR22			
<p>JR 36</p>	75 V				P2-0V75JR36	POV75JR36	

SLED NEEDLE – AIGUILLE A GLISSIERE

<p>SKI 22</p>	20 V			P3-0V20SKI22	P2-0V20SKI22		
---------------	-------------	--	--	--------------	--------------	--	--

STRAIGHT - DROIT

<p>GR 19</p>	20 V		P4-0V20GR19				
--------------	-------------	--	-------------	--	--	--	--



Gey910

Genko


ITALIA

TAPER POINT
BLUNT POINT/PROTECTED POINT










CU VARF ASCUTIT
VARF ROTUND BONT

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	3-0	2-0	0	1	2	3
		(2)	(3)	(3.5)	(4)	(5)	(6)

3/8 BENDING - CURBURA

	100 V			POV100DRN65	P1V100DRN65		
---	--------------	--	--	-------------	-------------	--	--

1/2 BENDING - CURBURA






	75 V	P3-0V75HRN30	P2-0V75HRN30				
	75 V	P3-0V75HRN36	P2-0V75HRN36	POV75HRN36			
	90 V		P2-0V90HRN37H	POV90HRN37H	P1V90HRN37H		
 <p>HEAVY - RAMFORSAT</p>	75 V		P2-0V75HRN37H				
	75 V			POV75HRN40	P1V75HRN40		
	90 V			POV90HRN40H	P1V90HRN40H	P2V90HRN40H	
 <p>HEAVY - RAMFORSAT</p>							
	90 V			POV90HRN45	P1V90HRN45	P2V90HRN45	
	90V			POV90HRN48	P1V90HRN48	P2V90HRN48	



Gey910

Genko
ITALIA



**TAPER CUTTING
CU TAIETURA ASCUTITA**



DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP					
	cm COLOR CULOARE	3-0	2-0	0	1	2
		(2)	(3)	(3.5)	(4)	(5)
1/2 BENDING - CURBURA						
 <p>HTC 40</p>	75 V		P2-0V75HTC40	POV75HTC40	P1V75HTC40	
	90 V		P2-0V90HTC40	POV90HTC40	P1V90HTC40	
 <p>HTC 40 H</p> <p>HEAVY - RAMFORSAT</p>	75 V		P2-0V75HTC40H	POV75HTC40H	P1V75HTC40H	
	90 V		P2-0V90HTC40H	POV90HTC40H	P1V90HTC40H	
 <p>HTC 45</p>	75 V		P2-0V75HTC45	POV75HTC45	P1V75HTC45	P2V75HTC45
 <p>HTC 48 H</p> <p>HEAVY - RAMFORSAT</p>	90 V			POV90HTC48H	P1V90HTC48H	P2V90HTC48H
 <p>HTC 80 H</p> <p>HEAVY - RAMFORSAT</p>	75 V			POV75HTC80H	P1V75HTC80H	





Gey910

SPATULA SPATULA

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP							
	cm COLOR CULOARE	10-0	9-0	8-0	7-0	6-0	5-0	4-0
		(0.2)	(0.3)	(0.4)	(0.5)	(0.7)	(1)	(1.5)
1/4 BENDING - CURBURA								
 VSP 8 D 	20 V					P6-0V20VSP8D		
	45 I					P6-0I45VSP8D	P5-0I45VSP8D	
	45 V					P6-0V45VSP8D	P5-0V45VSP8D	P4-0V45VSP8D

3/8 BENDING - CURBURA								
 DSP 6 	10 V	P10-0V10DSP6						
	45 I					P6-0I45DSP11D	P5-0I45DSP11D	P4-0I45DSP11D







1/2 BENDING - CURBURA								
 HSP 8 D 	45 V					P6-0V45HSP8D	P5-0V45HSP8D	
	45 I					P6-0I45HSP8D		
	20 V					P6-0V20HSP8D		

SPATULA

PRECISION POINT/MICRO POINT

SPATULA

PRECIZIE

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP					
	cm COLOR CULOARE	10-0	9-0	8-0	7-0	6-0
		(0.2)	(0.3)	(0.4)	(0.5)	(0.7)
3/8 BENDING - CURBURA						
 DSPM 6 	15 V	P10-0V15DSPM6	P9-0V15DSPM6	P8-0V15DSPM6		
	10 V	P10-0V10DSPM6	P9-0V10DSPM6			
 DSPM 6.6 D 	45 V			P8-0V45DSPM6.6D		
	30 V			P8-0V30DSPM6.6D	P7-0V30DSPM6.6D	
1/2 BENDING - CURBURA						
 HSPM 7 D 	45 V				P7-0V45HSPM7D	
	30 V			P8-0V30HSPM7D		