



*Synthetic non absorbable polypropylene suture.  
Monofilament.*

**CHARACTERISTICS**

Excellent fluency  
Excellent knot tying  
Excellent tensile strength  
Perfect caliber uniformity  
Minimum Tissue reaction  
No capillarity

**INDICATIONS**

KeyLene is indicated for use in superficial soft tissues. Approximation, cardiovascular surgery, ophthalmic, neurological procedures and for hernia mesh fixing.

**IN VIVO TENSILE STRENGTH**

Fixed (permanent)

**STERILIZATION**

ETO (Ethylene Oxide)

**COLORING**

Blue



*Sutura sintetica neabsorbabila din polipropilena.  
Monofilament.*

**CARACTERISTICI**

Fluiditate excelenta la traversarea tesuturilor  
Plasticitate excelenta si rezistenta a nodului  
Rezistenta la tractiune (rupere) mare  
Diametru uniform  
Reactie minima a tesutului  
Fara capilaritate

**INDICATII**

Suturile chirurgicale KeyLene sunt indicate pentru apropierea tesuturilor moi, in chirurgia cardiovasculara, oftalmologica, neurologica si plastic si pentru fixarea paselor pentru hernia.

**REZISTENTA LA TRACTIUNE (RUPERE)**

Permanentă

**STERILIZARE**







ETO (oxid de etilena)



**CULOARE**




Albastru



## REVERSE CUTTING CU TAIETURA IN EXTERIOR

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP							
	cm COLOR CULOARE	6-0 (0.7)	5-0 (1)	4-0 (1.5)	3-0 (2)	2-0 (3)	0 (3.5)	1 (4)
	<b>3/8 BENDING - CURBURA</b>							
▼  DS 16	75 B	SL6-0B75DS16	SL5-0B75DS16	SL4-0B75DS16				
▼  DS 19	45 B		SL5-0B45DS19	SL4-0B45DS19	SL3-0B45DS19			
	75 B		SL5-0B75DS19	SL4-0B75DS19	SL3-0B75DS19			
▼  DS 24	75 B			SL4-0B75DS24	SL3-0B75DS24	SL2-0B75DS24		
▼  DS 26	45 B				SL3-0B45DS26	SL2-0B45DS26		
	75 B				SL3-0B75DS26	SL2-0B75DS26		
▼  DS 30	75 B				SL3-0B75DS30	SL2-0B75DS30	SL0B75DS30	
▼  DS 39	75 B					SL2-0B75DS39	SL0B75DS39	SL1B75DS39
	cm COLOR CULOARE	4-0 (1.5)	3-0 (2)	2-0 (3)	0 (3.5)	1 (4)	2 (3)	

<b>1/2 BENDING - CURBURA</b>								
▼  HS 40H HEAVY - RAMFORSAT	100 B				SL0B100HS40H	SL1B100HS40H		
▼  HS 48H HEAVY - RAMFORSAT	100 B				SL0B100HS48H	SL1B100HS48H	SL2B100HS48H	

<b>STRAIGHT - DREPT</b>								
▼  GS 55	90 B			SL2-0B90GS55				
▼  GS 60	75 B	SL4-0B75GS60	SL3-0B75GS60	SL2-0B75GS60				
▼  GS 75	75 B		SL3-0B75GS75	SL2-0B75GS75	SL0B75GS75			



**REVERSE CUTTING**  
PRECISION POINT/MICRO POINT

**CU TAIETURA IN EXTERIOR**  
TRIUNGHI INVERS (VARF IN JOS) PRECIZIE

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP							
	cm COLOR CULDARE	8-0 (0.4)	7-0 (0.5)	6-0 (0.7)	5-0 (1)	4-0 (1.5)	3-0 (2)	2-0 (3)
	<b>3/8 BENDING - CURBURA</b>							
DSM 7	45 B	SL8-0B45DSM7	SL7-0B45DSM7	SL6-0B45DSM7				
DSM 8	45 B		SL7-0B45DSM8	SL6-0B45DSM8				
DSM 11	45 B			SL6-0B45DSM11	SL5-0B45DSM11			
DSM 13	45 B			SL6-0B45DSM13	SL5-0B45DSM13	SL4-0B45DSM13		
	75 B			SL6-0B75DSM13	SL5-0B75DSM13	SL4-0B75DSM13		
DSM 16	45 B			SL6-0B45DSM16	SL5-0B45DSM16	SL4-0B45DSM16		
	75 B			SL6-0B75DSM16	SL5-0B75DSM16	SL4-0B75DSM16		
DSM 19	45 B				SL5-0B45DSM19	SL4-0B45DSM19	SL3-0B45DSM19	
	75 B				SL5-0B75DSM19	SL4-0B75DSM19	SL3-0B75DSM19	
DSM 24	45 B					SL4-0B45DSM24	SL3-0B45DSM24	SL2-0B45DSM24
DSM 26	45 B						SL3-0B45DSM26	SL2-0B45DSM26

**CONVENTIONAL CUTTING**  
PRECISION POINT/MICRO POINT

**CU TAIETURA CONVENTIONALA**  
TRIUNGHI CONVENTIONAL (VARF IN SUS) PRECIZIE

<b>3/8 BENDING - CURBURA</b>								
DCM 16	45 B			SL6-0B45DCM16	SL5-0B45DCM16	SL4-0B45DCM16	SL3-0B45DCM16	
DCM 19	45 B				SL5-0B45DCM19	SL4-0B45DCM19	SL3-0B45DCM19	
DCM 26	45 B			SL6-0B45DCM26	SL5-0B45DCM26	SL4-0B45DCM26	SL3-0B45DCM26	
DCM 36	75 B						SL3-0B75DCM36	
DCM 40	100 B							SL2-0B100DCM40



## TAPER POINT CU VARF ASCUTIT

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	<b>8-0</b>	<b>7-0</b>	<b>6-0</b>	<b>5-0</b>	<b>4-0</b>	<b>3-0</b>
		(0.4)	(0.5)	(0.7)	(1)	(1.5)	(2)

### 3/8 BENDING - CURBURA











	<b>45 B</b>	SL8-OB45DR7D					
	<b>60 B</b>	SL8-OB60DR7D	SL7-OB60DR7D				
	<b>75 B</b>		SL7-OB75DR9	SL6-OB75DR9			
	<b>45 B</b>		SL7-OB45DR9D	SL6-OB45DR9D			
	<b>60 B</b>		SL7-OB60DR9D	SL6-OB60DR9D	SL5-OB60DR9D		
	<b>60 B</b>		SL7-OB60DR11D	SL6-OB60DR11D	SL5-OB60DR11D		
	<b>75 B</b>			SL6-OB75DR13	SL5-OB75DR13		
	<b>60 B</b>		SL7-OB60DR13D	SL6-OB60DR13D	SL5-OB60DR13D		
	<b>75 B</b>		SL7-OB75DR13D	SL6-OB75DR13D	SL5-OB75DR13D	SL4-OB75DR13D	
	<b>75 B</b>					SL4-OB75DR17	SL3-OB75DR17
	<b>75 B</b>				SL5-OB75DR17D	SL4-OB75DR17D	SL3-OB75DR17D

### 1/2 BENDING - CURBURA

	<b>60 B</b>				SL5-OB60HR11D		
	<b>60 B</b>			SL6-OB60HR13D	SL5-OB60HR13D	SL4-OB60HR13D	
	<b>75 B</b>			SL6-OB75HR13D	SL5-OB75HR13D		
	<b>75 B</b>				SL5-OB75HR17	SL4-OB75HR17	SL3-OB75HR17



## TAPER POINT CU VARF ASCUTIT







DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	6-0 (0.7)	5-0 (1)	4-0 (1.5)	3-0 (2)	2-0 (3)	0 (3.5)
<b>1/2 BENDING - CURBURA</b>							
 HR 17 D	75 B	SL6-0B75HR17D	SL5-0B75HR17D	SL4-0B75HR17D	SL3-0B75HR17D		
	90 B	SL6-0B90HR17D	SL5-0B90HR17D	SL4-0B90HR17D	SL3-0B90HR17D		
 HR 20 D	90 B			SL4-0B90HR20D	SL3-0B90HR20D		
 HR 22	75 B			SL4-0B75HR22	SL3-0B75HR22		
 HR 22 D	75 B			SL4-0B75HR22D	SL3-0B75HR22D		
	90 B			SL4-0B90HR22D	SL3-0B90HR22D		
 HR 26	75 B				SL3-0B75HR26	SL2-0B75HR26	SLOB75HR26
 HR 26 D	75 B		SL5-0B75HR26D	SL4-0B75HR26D	SL3-0B75HR26D	SL2-0B75HR26D	
	90 B		SL5-0B90HR26D	SL4-0B90HR26D	SL3-0B90HR26D	SL2-0B90HR26D	
	120 B			SL4-0B120HR26D	SL3-0B120HR26D	SL2-0B120HR26D	
	cm COLOR CULOARE	4-0 (1.5)	3-0 (2)	2-0 (3)	0 (3.5)	1 (4)	2 (5)
 HR 27 H HEAVY - RAMFORSAT	75 B			SL2-0B75HR27H	SLOB75HR27H	SL1B75HR27H	
 HR 30	75 B			SL2-0B75HR30	SLOB75HR30		
 HR 30 H HEAVY - RAMFORSAT	100 B				SLOB100HR30H		
 HR 30 D	90 B		SL3-0B90HR30D	SL2-0B90HR30D			
	120 B		SL3-0B120HR30D				



# KeyLene





## TAPER POINT CU VARF ASCUTIT

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	<b>4-0</b> (1.5)	<b>3-0</b> (2)	<b>2-0</b> (3)	<b>0</b> (3.5)	<b>1</b> (4)	<b>2</b> (5)
	<b>1/2 BENDING - CURBURA</b>						
 HR 37	<b>75 B</b>			SL2-0B75HR37	SL0B75HR37	SL1B75HR37	
 HR 37 H HEAVY - RAMFORSAT	<b>75 B</b>			SL2-0B75HR37H	SL0B75HR37H	SL1B75HR37H	
 HR 40 H HEAVY - RAMFORSAT	<b>75 B</b> <b>100 B</b>			SL2-0B75HR40H		SL1B75HR40H	
					SL0B100HR40H	SL1B100HR40H	
 HR 40 D	<b>90 B</b>		SL3-0B90HR40D	SL2-0B90HR40D			
 HR 48 H HEAVY - RAMFORSAT	<b>75 B</b>				SL0B75HR48H	SL1B75HR48H	SL2B75HR48H
 HR 65 H	<b>100 B</b>					SL1B100HR65	



## TAPER POINT BLUNT POINT/PROTECTED POINT

## CU VARF ASCUTIT VARF ROTUND BONT

<b>1/2 BENDING - CURBURA</b>							
 HRN 40	<b>100 B</b>					SL1B100HRN40	
 HRN 45	<b>100 B</b>					SL1B100HRN45	



# KeyLene

# Genko

**TAPER POINT**  
PRECISION POINT/MICRO POINT

**CU VARF ASCUTIT**  
VARF ROTUND PRECIZIE

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP					
	cm COLOR CULOARE	10-0 (0.2)	9-0 (0.3)	8-0 (0.4)	7-0 (0.5)	6-0 (0.7)
	<b>3/8 BENDING - CURBURA</b>					
⊙ <b>DRM 4</b> 	<b>13 B</b>	SL10-0B13DRM4				
⊙ <b>DRM 5</b> 	<b>13 B</b>	SL10-0B13DRM5	SL9-0B13DRM5			
⊙ <b>DRM 6 D</b> 	<b>45 B</b>			SL8-0B45DRM6D		
	<b>60 B</b>			SL8-0B60DRM6D	SL7-0B60DRM6D	
	<b>75 B</b>			SL8-0B75DRM6D	SL7-0B75DRM6D	
⊙ <b>DRM 8 D</b> 	<b>60 B</b>			SL8-0B60DRM8D	SL7-0B60DRM8D	
⊙ <b>DRM 9 D</b> 	<b>60 B</b>				SL7-0B60DRM9D	SL6-0B60DRM9D



**TAPER CUTTING**  
CU TAIETURA ASCUTITA

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP						
	cm COLOR CULOARE	7-0 (0.5)	6-0 (0.7)	5-0 (1)	4-0 (1.5)	3-0 (2)	2-0 (3)
	<b>3/8 BENDING - CURBURA</b>						
⊙ <b>DTC 9 D</b> 	<b>45 B</b>	SL7-0B45DTC9D	SL6-0B45DTC9D				
	<b>60 B</b>	SL7-0B60DTC9D	SL6-0B60DTC9D				
	<b>75 B</b>		SL6-0B75DTC9D				
⊙ <b>DTC 17</b> 	<b>75 B</b>			SL5-0B75DTC17	SL4-0B75DTC17		
⊙ <b>DTC 17 D</b> 	<b>75 B</b>			SL5-0B75DTC17D	SL4-0B75DTC17D		


## TAPER CUTTING CU TAIETURA ASCUTITA

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP					
	cm COLOR CULOARE	6-0	5-0	4-0	3-0	2-0
		(0.7)	(1)	(1.5)	(2)	(3)

### 3/8 BENDING - CURBURA

	<b>75 B</b>			SL4-0B90DTC26D		
	<b>120 B</b>			SL4-0B120DTC26D		

### 1/2 BENDING - CURBURA


	<b>75 B</b>			SL4-0B75HTC17	SL3-0B75HTC17	SL2-0B75HTC17
---	-------------	--	--	---------------	---------------	---------------


	<b>90 B</b>		SL5-0B90HTC17D	SL4-0B90HTC17D	SL3-0B90HTC17D	SL2-0B90HTC17D
---	-------------	--	----------------	----------------	----------------	----------------

cm COLOR CULOARE	4-0	3-0	2-0	0	1
	(0.7)	(1)	(1.5)	(2)	(3)

	<b>75 B</b>		SL3-0B75HTC26	SL2-0B75HTC26		
---	-------------	--	---------------	---------------	--	--

	<b>90 B</b>		SL3-0B90HTC26D	SL2-0B90HTC26D	SL0B90HTC26D	
---	-------------	--	----------------	----------------	--------------	--

	<b>100 B</b>				SLOB100HTC37	
---	--------------	--	--	--	--------------	--

	<b>100 B</b>					SL1B100HTC45
---	--------------	--	--	--	--	--------------



## SPATULA SPATULA

DESCRIPTION	USP CALIBER (metric) – DIAMETRUL FIRULUI USP					
	cm COLOR CULOARE	10-0	9-0	8-0	7-0	6-0
		(0.2)	(0.3)	(0.4)	(0.5)	(0.7)

### 3/8 BENDING - CURBURA

	<b>15 B</b>	SL10-0B15DSP7D	SL9-0B15DSP7D			
---	-------------	----------------	---------------	--	--	--